




浙江益瑞新能源有限公司

PV SOLAR CABLE & ACCESSORIES BROCHURE

浙江益瑞新能源有限公司


ZHEJIANG YRO NEW ENERGY CO.,LTD.

Photovoltaic Power System




Single Core

PV Cable



Double core

PV Cable



2PFG1169/08.07 PV1-F Solar Cable

APPLICATION

Flexible cables suitable for PV solar DC current systems. The max allowable DC voltage 1.8 kV (Conductor to conductor, system without earth). Used at security level II location. These cables are allowed to be connected in a multi-structural manner. The cable is designed for operation at temperature up to 90°C.

TECHNICAL INDICATORS

Nominal voltage: U₀/U 0.6/1KV(AC) 1800DC(non-load)
 Test voltage: AC6.5KV/5min(20°C±0.5)
 or DC15KV/5min (20°C±0.5) without breakdown
 Ambient temperature: -40°C~+90°C
 Conductor maximum temperature: 120°C
 Maximum short circuit temperature: ≤250°C/5S
 Expected service life: 25 years
 Bending radius: ≥4D

STRUCTURE

Conductor: Tinned copper flexible conductor of Class 5 in 2Pfg1169
 Insulation: LSZH electron-beam cross-linked Polyolefin (125°C)
 Sheath: LSZH electron-beam cross-linked Polyolefin (125°C)
 Color: red or black

CHARACTERISTICS COMPLIANCE

Fire-resistance: EN 60332-1-2
 Acid and alkali solution: EN 60811-2-1
 Halogen determination: EN 50267/EN 60684
 Weather resistance/UV resistance: HD 605/A1
 Compliance certification: ROHS TUV
 Executive standard: 2 Pfg 1169/08.2007

Structural dimensions and parameters

Model	Specification (mm ²)	Insulation Nominal Thickness (mm)	Sheath Nominal Thickness (mm)	Approximate outer diameter (mm)	Maximum DC resistance of conductor at 20°C (Ω/km)	Minimum insulation resistance at 90°C (MΩ/km)
PV1-F	2.5	≥0.5	≥0.5	4.2	8.21	0.69
PV1-F	4.0	≥0.5	≥0.5	5.9	5.09	0.58
PV1-F	4.0	≥0.5	≥0.5	4.65	5.09	0.58
PV1-F	4.0	≥0.5	≥0.5	5.5	5.09	0.58
PV1-F	6.0	≥0.5	≥0.5	6.2	3.39	0.50
PV1-F	6.0	≥0.5	≥0.5	5.35	3.39	0.50
PV1-F	10	≥0.5	≥0.5	7.3	1.95	0.42
PV1-F	16	≥0.5	≥0.5	8.5	1.24	0.34
PV1-F	25	0.9	1.0	10.6	0.795	0.34
PV1-F	35	0.9	1.1	12.5	0.565	0.29
PV1-F	50	1.0	1.2	14.2	0.393	0.27
PV1-F	2X2.5	≥0.5	≥0.5	5.2X10.9	8.21	0.69
PV1-F	2X4.0	≥0.5	≥0.5	5.9X12.2	5.09	0.58
PV1-F	2X4.0	≥0.5	≥0.5	5.5X11.4	5.09	0.58
PV1-F	2X4.0	≥0.5	≥0.5	4.85X10	5.09	0.58
PV1-F	2X6.0	≥0.5	≥0.5	6.2X12.9	3.39	0.50
PV1-F	2X6.0	≥0.5	≥0.5	5.35X11.2	3.39	0.50
PV1-F	2X10.0	≥0.5	≥0.5	7.3X15.1	1.95	0.42

Reference table for quick selection of carrying capacity

Cross-sectional area	Recommended value of ampacity (A)	Download traffic conversion factor for different ambient temperatures	
Copper conductor	Laying in the air	Ambient temperature °C	Conversion factor
2.5	41	10	1.15
4	55	20	1.08
6	70	30	1.0
10	98	40	0.91
16	132	50	0.82
25	176	70	0.58
35	218	80	0.41
50	276		
2X2.5	33	60	0.71
2X4	44	70	0.58
2X6	57	80	0.41
2X10	79		
2X16	107		

erature is 30°C; conductor maximum temperature is 90°C

Note: Ambient temp

PRODUCT CHARACTERISTICS

UV and ozone resistant, hydrolysis resistant
 High temperature resistance, service life of more than 25 years
 Good flexibility, easy installation and laying
 Halogen-free and low-smoke material, in line with environmental protection requirements
 Compatible with all common connectors

传世界·创未来

TRANSMISSION TO WORLD AND CREATE THE FUTURE

INTELLIGENT POWER TECHNOLOGY



浙江益瑞新能源有限公司

ZHEJIANG YRO NEW ENERGY CO.,LTD.



Address: No. 463, Guang'an Road, Wuniu Sub-district,
Yongjia County, Wenzhou City, Zhejiang Province, China.



Website: <https://www.yroenergy.com/>



Tel: 0577-62963009



Tel: 18657776197



Mail: info@yroele.com